



# Knudsen Kilen

## Data Sheet Combi Extension



Extension component for the Combi and Combi Max series which increases the module height with 35 mm per piece. A maximum of 5 Combi Extensions can be used per module.

In addition, Combi Sole, Combi Sound Reducer and Combi Sound Reducer Light can all be used with Combi Extension.

## Technical information

| Properties                                    | Specifications                                 | Remarks                                                                    |
|-----------------------------------------------|------------------------------------------------|----------------------------------------------------------------------------|
| Item number                                   | 975108120                                      |                                                                            |
| Material                                      | LDPE (Low Density Polyethylene)                |                                                                            |
| Width / Length                                | 80 / 100 mm                                    |                                                                            |
| Height                                        | 35 mm                                          |                                                                            |
| Color                                         | Anthracite grey                                |                                                                            |
| Weight                                        | 57 grams                                       |                                                                            |
| Temperature High (Softing Point)              | 95 °C                                          |                                                                            |
| Temperature Low (Low Temperature Brittleness) | -73 °C                                         |                                                                            |
| UV resistance                                 | UV additive added in masterbatch               |                                                                            |
| Aging effect                                  | At 75 years, no change is seen in the material | The wedge has been tested at 20 degrees according to work standard SPF2000 |
| Point load                                    | 250 kg                                         | With Combi Max series at flat pressure 40x40 mm                            |
| Surface load                                  | 1.500 kg                                       | Per m2 floor when using 6 sets of wedges per m2                            |
| Consumption per m2                            | 6 pieces                                       | When leveling joist floors                                                 |
| Moisture                                      | Is not affected by moisture, rot og fungus     |                                                                            |
| Fire                                          | Does not emit toxic fumes in case of fire      |                                                                            |
| Fire classification                           | Fuel class B2 / DIN 4102-1                     |                                                                            |
| Capillary breaking                            | Yes                                            |                                                                            |



## Knudsen Kilen

Knudsen Kilen A/S • Industrivej 21 • DK - 3300 Frederiksvaerk • tel.: +45 47 76 01 01  
info@knudsenkilen.dk • www.knudsenkilen.dk

Follow us on **LinkedIn**