

Knudsen Kilen

Data Sheet Combi Top Small





Combi series for blocking up wooden floor on joists.

Combi Top Small is used together with Combi Base, but can alternatively be used with Combi Top Medium or Combi Top Large as a base wedge and also with the Combi Top Sound Wedges for better step sound reduction. Blocking up heights when used with Combi Base is 32-48 mm and further up to 223 mm With Combi Extension. Blocking up heights together with: Combi Top Medium: 19-40 mm / Combi Top Large: 31-53 mm.

Technical information

Properties	Specifications	Remarks
Item number	975308120	
Material	LDPE (Low Density Polyethylene)	
Width / Length	43 / 80 mm	
Height	3 - 19 mm	
Color	Light green	
Weight	13 grams	
Temperature High (Softing Point)	95 ℃	
Temperature Low (Low Temperature Brittleness)	-73 ℃	
UV resistance	UV additive added in masterbatch	
Aging effect	At 75 years, no change is seen in the material	The wedge has been tested at 20 degrees according to work standard SPF2000
Point load	250 kg	With an overlap of 35-100% together with a Yellow Wedge
Surface load	1.500 kg	Per m2 floor when using 6 sets of wedges per m2
Consumption per m2	6 pieces	When leveling joist floors
Moisture	Is not affected by moisture, rot og fungus	3
Fire	Does not emit toxic fumes in case of fire	
Fire classification	Fuel class B2 / DIN 4102-1	
Capillary breaking	Yes	



