



Knudsen Kilen

Data Sheet K-Block 45 2 mm



The K-Block 45 series is designed to accurately fit the width of rafters and other planed 2" wood, but is also used for distance adjustment and leveling of medium-heavy tasks such as doors and windows.

The countersunk screw holes provide secure mounting.

All sizes (2, 3, 5, 10 and 20 mm) can merge together to form a singular block with the desired height.

K-Block 45 cannot be used together with K-Block 6T.

Technical information

Properties	Specifications	Remarks
Item number	985004054S	
Material	HDPE (High Density Polyethylene)	
Width / Length	45 / 80 mm	
Thickness	2 mm	
Color	Black	
Weight	5 grams	
Temperature High (Softing Point)	120 °C	
Temperature Low (Low Temperature Brittleness)	-76 °C	
UV resistance	UV additive added in masterbatch	
Pressure load	2,000 kg	
Moisture	Is not affected by moisture, rot og fungus	
Fire	Does not emit toxic fumes in case of fire	
Fire classification	Fuel class B2 / DIN 4102-1	
Capillary breaking	Yes	



Knudsen Kilen

Knudsen Kilen A/S • Industrivej 21 • DK - 3300 Frederiksvaerk • tel.: +45 47 76 01 01
info@knudsenkilen.dk • www.knudsenkilen.dk

Follow us on [LinkedIn](#)