



Knudsen Kilen

Data Sheet K-Block 45 20 mm



The K-Block 45 series is designed to accurately fit the width of rafters and other planed 2" wood, but is also used for distance adjustment and leveling of medium-heavy tasks such as doors and windows.

The countersunk screw holes provide secure mounting.

All sizes (2, 3, 5, 10 and 20 mm) can merge together to form a singular block with the desired height.

K-Block 45 cannot be used together with K-Block 6T.

Technical information

| Properties | Specifications | Remarks |
|---|--|---------|
| Item number | 985004058S | |
| Material | HDPE (High Density Polyethylene) | |
| Width / Length | 45 / 80 mm | |
| Thickness | 20 mm | |
| Color | Black | |
| Weight | 36 grams | |
| Temperature High (Softing Point) | 120 °C | |
| Temperature Low (Low Temperature Brittleness) | -76 °C | |
| UV resistance | UV additive added in masterbatch | |
| Pressure load | 2,000 kg | |
| Moisture | Is not affected by moisture, rot og fungus | |
| Fire | Does not emit toxic fumes in case of fire | |
| Fire classification | Fuel class B2 / DIN 4102-1 | |
| Capillary breaking | Yes | |



Knudsen Kilen

Knudsen Kilen A/S • Industrivej 21 • DK - 3300 Frederiksvaerk • tel.: +45 47 76 01 01
info@knudsenkilen.dk • www.knudsenkilen.dk

Follow us on [LinkedIn](#)