



Knudsen Kilen

Data Sheet K-Block 45C 20 mm blue



The K-Block 45C series has the same properties and functions as K-Block 45, but is simply in color-coded thicknesses. With its 45 mm, K-Block 45C is designed to accurately fit the width of rafters and other planed 2" wood, but is also used for distance adjustment and leveling of medium-heavy tasks such as doors and windows. The countersunk screw holes provide secure mounting.

All sizes (2, 3, 5, 10 and 20 mm) of both K-Block 45/45C can merge together to form a singular block with the desired height. K-Block 45 cannot be used together with K-Block 6T.

Technical information

Properties	Specifications	Remarks
Item number	985004074	
Material	HDPE (High Density Polyethylene)	
Width / Length	45 / 80 mm	
Thickness	20 mm	
Color	Blue	
Weight	36 grams	
Temperature High (Softing Point)	120 °C	
Temperature Low (Low Temperature Brittleness)	-76 °C	
UV resistance	UV additive added in masterbatch	
Pressure load	2,000 kg	
Moisture	Is not affected by moisture, rot og fungus	
Fire	Does not emit toxic fumes in case of fire	
Fire classification	Fuel class B2 / DIN 4102-1	
Capillary breaking	Yes	



Knudsen Kilen

Knudsen Kilen A/S • Industrivej 21 • DK - 3300 Frederiksværk • tel.: +45 47 76 01 01
info@knudsenkilen.dk • www.knudsenkilen.dk

Follow us on **LinkedIn**