

Knudsen Kilen

Data Sheet Knudsen Terrace Raiser



Knudsen Terrace System is used for the modular building of terraces using joists made from timber or a composite material. The system is UV-resistant, frost-proof and will not be damaged by water. Knudsen Terrace Raiser is a supplement to the Knudsen Terrace Kit for use in raising the module up to 287 mm when using a maximum of 5 Terrace Raisers.

Technical information

Properties	Specifications	Remarks
Item number	8701831K	
Content per box	50 pieces	
Material	LDPE (Low Density Polyethylene)	
Width / Length	80 / 100 mm	
Height	35 mm	
Color	Anthracite grey	
Weight	57 grams	
Temperature High (Softing Point)	95 °C	
Temperature Low (Low Temperature Brittleness)	-73 °C	
UV resistance	UV additive added in masterbatch	
Point load	250 kg	At flat pressure 40x40 mm
Surface load	1.250 kg	Per m2 floor when using 5 sets of Knudsen Terrace Kits per m2
Consumption per m2	5 pieces per m2	For terrace deck leveling
Moist	Is not affected by moisture, rot or fungus	
Fire	Does not emit toxic fumes in case of fire	
Fire classification	Fuel class B2 / DIN 4102-1	
Capillary breaking	Yes	



 **Knudsen Kilen**

Knudsen Kilen A/S • Industrivej 21 • DK - 3300 Frederiksvaerk • tel.: +45 47 76 01 01
info@knudsenkilen.dk • www.knudsenkilen.dk

Follow us on 