



Knudsen Kilen

Data Sheet Knudsen Terrace Wedge



Knudsen Terrace System is used for the modular building of terraces using joists made from timber or a composite material. The system is UV-resistant, frost-proof and will not be damaged by water. With a set of Knudsen Terrace Wedges, the blocking up heights range from 27-40 mm.

Technical information

Properties	Specifications	Remarks
Item number	8701832K	
Content per box	100 pieces / 50 sets	
Material	LDPE (Low Density Polyethylene)	
Width / Length	45 / 150 mm	
Height	25 mm	At the highest point
Color	Black	
Weight	34 grams	
Temperature High (Softing Point)	95 °C	
Temperature Low (Low Temperature Brittleness)	-73 °C	
UV resistance	UV additive is added to the wedge in the masterbatch	
Point load	760 - 2200 kg	With an overlap of 35-100%
Surface load	3.800 - 11.000 kg	Per m2 deck when using 5 sets of Terrace Wedges per m2
Consumption per m2	5 sets per m2	When leveling decks on joists
Moisture	Is not affected by moisture, rot or fungus	
Fire	Does not emit toxic fumes in case of fire	
Fire classification	Fuel class B2 / DIN 4102-1	
Capillary breaking	Yes	



Knudsen Kilen

Knudsen Kilen A/S • Industrivej 21 • DK - 3300 Frederiksvaerk • tel.: +45 47 76 01 01
info@knudsenkilen.dk • www.knudsenkilen.dk

Follow us on **LinkedIn**