Knudsen Kilen

Data Sheet Fix Shim 12 mm



Knudsen Fix Shims spacer blocks are suitable for all types of tasks where items need to be stabilized, e.g. when installing doors and windows, setting up kitchen and bathroom elements, moldings, panels, etc. As the Fix Shim is designed as a split piece with fins, which ensures a stable grip on the screw during any assembly, it is particularly suitable for mounting on vertical surfaces. Fix Shims cannot be used for heavy leveling tasks such as floors, rafters etc.

Technical information

| Properties | Specifications | Remarks |
|--|--|--|
| Item number | 973305012 | |
| Material | HDPE (High Density Polyethylene) | |
| Width / Length | 45 / 75 mm | |
| Height | 12 mm | |
| Color | Orange | |
| Weight | 8,8 grams | |
| Temperature High (Softing Point) | 120 °C | |
| Temperature Low (Low Temperature Brittleness) | -76 °C | |
| UV resistance | UV additive added in masterbatch | |
| Aging effect | At 75 years, no change is seen in the material | The wedge has been tested at 20 degrees according to work standard SPF2000 |
| Surface load | 200 kg | |
| Moisture | Is not affected by moisture, rot og fungus | |
| Fire | Does not emit toxic fumes in case of fire | |
| Fire classification | Fuel class B2 / DIN 4102-1 | |
| Capillary breaking | Yes | |

